

Avvisatori acustici industriali

Industrial horns


V 12-24-48-110-240 (±10%)		~ 50/60 Hz	On ∞	autoestinguente self-extinguishing
IP 65			Hz 300÷350	°C -30 +40



Suono continuo Single sound

V ~	12	24	48	110	240
mA	830	415	210	90	42
dB(A)1m	95	95	95	95	95

MS12A	53002	MS110A	53008
MS24A	53003	MS240A	53015
MS48A	53005		




Kg. 0,31



Suono intermittente Intermittent sound

V ~	12	24	48	110	240
mA	850	430	220	95	45
dB(A)1m	95	95	95	95	95

MSSI12A	53530	MSSI110A	53533
MSSI24A	53531	MSSI240A	53535
MSSI48A	53532		




Kg. 0,38



Suono continuo Single sound

V ~	12	24	48	110	240
mA	830	415	210	90	42
dB(A)1m	95	95	95	95	95

MSSD12A	53050	MSSD110A	53054
MSSD24A	53051	MSSD240A	53057
MSSD48A	53053		




Kg. 0,33



Suono intermittente Intermittent sound

V ~	12	24	48	110	240
mA	850	430	220	95	45
dB(A)1m	95	95	95	95	95

MSSDSI12A	53551	MSSDSI110A	53554
MSSDSI24A	53552	MSSDSI240A	53556
MSSDSI48A	53553		



Kg. 0,39



Suono continuo Single sound


V ~	12	24	48	110	240
mA	830	415	210	90	42
dB(A)1m	95	95	95	95	95

MSR12A	53537	MSR110A	53540
MSR24A	53538	MSR240A	53542
MSR48A	53539		

Suono intermittente Intermittent sound

V ~	12	24	48	110	240
mA	850	430	220	95	45
dB(A)1m	95	95	95	95	95

MSRSI12A	53544	MSRSI110A	53547
MSRSI24A	53545	MSRSI240A	53549
MSRSI48A	53546		



Kg. 0,42



Suono continuo Single sound


V ~	12	24	48	110	240
mA	830	415	210	90	42
dB(A)1m	95	95	95	95	95

MSSDR12A	53558	MSSDR110A	53561
MSSDR24A	53559	MSSDR240A	53563
MSSDR48A	53560		

Suono intermittente Intermittent sound

V ~	12	24	48	110	240
mA	850	430	220	95	45
dB(A)1m	95	95	95	95	95

MSSDRSI12A	53565	MSSDRSI110A	53568
MSSDRSI24A	53566	MSSDRSI240A	53570
MSSDRSI48A	53567		



Kg. 0,42

Per ordinare l'opzione nera vedere codici su listino in vigore. Black option available on request.

Industrial horns

V12-24-48-110-240 (±10%)	==	~ 50/60 Hz	On ∞
autoestinguente self-extinguishing	IP 54	🎵 ---	°C -30 +40



M 16


SAI
SAI

⑪ ⑲

Suono continuo
Single sound

V 	12	24	48	V 	12	24	48	110	240
A	1.7	0.9	0.45	A	1.9	1.1	0.54	0.19	0.13
dB(A)1m	110	110	110	dB(A)1m	105	105	105	105	106
Hz	600÷20000			Hz	800÷15000				

SAI12D	42250	SAI48D	42254
SAI12A	42251	SAI48A	42255
SAI24D	42252	SAI110A	42257
SAI24A	42253	SAI240A	42259



Kg. 0,7



M 16


**SAI SI
SAISI**

11 19

Suono intermittente
Intermittent sound

V ~	12	24	48	110	240
A	1.9	1.1	0.54	0.19	0.13
dB(A)1m	105	105	105	105	106
Hz	800÷15000				

SAISI12A	42361	SAISI110A	42366
SAISI24A	42363	SAISI240A	42368
SAISI48A	42365		



Kg. 0,7



M 16

SAI SD
SAISD


11 20

Suono continuo
Single sound

V 	12	24	48		
A	1.7	0.9	0.45		
dB(A)1m	110	110	110		
Hz	600÷20000				

V 	12	24	48	110	240
A	1.9	1.1	0.54	0.19	0.13
dB(A)1m	105	105	105	105	106
Hz	800÷15000				

SAISD12D	42270	SAISD48D	42274
SAISD12A	42271	SAISD48A	42275
SAISD24D	42272	SAISD110A	42277
SAISD24A	42273	SAISD240A	42279



Kg. 0,7



M 16


SAI SD SI
SAISDSI

11 20

Suono intermittente
Intermittent sound

V ~	12	24	48	110	240
A	1.9	1.1	0.54	0.19	0.13
dB(A)1m	105	105	105	105	106
Hz	800÷15000				

SAISDSI12A	42370	SAISDSI110A	42375
SAISDSI24A	42372	SAISDSI240A	42377
SAISDSI48A	42374		



Kg. 0,7

Per ordinare l'opzione nera vedere codici su listino in vigore. Black option available on request.