

Luci xeno

Xenon flashing beacons

V 12÷24-110-240 (±10%)			50/60 Hz	J 1	Flash/min. 1F: 65±10 - 2F: 2x65±10				
IP 54		°C -30 +40	On			PC	autoestinguente self-extinguishing		




MXL1J1F
MXL1J2F

(13)

1F	V 		12÷24				2F	V 		12÷24				-	-
	V 							V 							
	mA		200	160	45	45		mA		200	160	70	65		
	Cd (p)		350	450	350	850		Cd (p)		350 300	450 300	350 200	850 750		
XENON 1J LRX 1J															

MXL1F1224DA1		64112	MXL1F110A3		64120	MXL2F1224DA1		64134	M
MXL1F1224DA2		64113	MXL1F110A5		64121	MXL2F1224DA2		64135	M
MXL1F1224DA3		64114	MXL1F240A1		64122	MXL2F1224DA3		64136	M
MXL1F1224DA4		64115	MXL1F240A2		64123	MXL2F1224DA4		64137	M
MXL1F1224DA5		64116	MXL1F240A3		64124	MXL2F1224DA5		64138	M
MXL1F1224DA6		64117	MXL1F240A4		64125	MXL2F1224DA6		64139	M
MXL1F110A1		64118	MXL1F240A5		64126	MXL2F110A2		64140	M
MXL1F110A2		64119	MXL1F240A6		64127				



Kg. 0,12

Per ordinare l'opzione nera richiedere i codici.
Code numbers for the black version are available on request.

MXL1F1224DA1	●	64112	MXL1F110A3	●	64120	MXL2F1224DA1	●	64134	MXL2F110A3	●	64141
MXL1F1224DA2	●	64113	MXL1F110A5	●	64121	MXL2F1224DA2	●	64135	MXL2F110A5	●	64142
MXL1F1224DA3	●	64114	MXL1F240A1	●	64122	MXL2F1224DA3	●	64136	MXL2F240A1	●	64146
MXL1F1224DA4	●	64115	MXL1F240A2	●	64123	MXL2F1224DA4	●	64137	MXL2F240A2	●	64143
MXL1F1224DA5	●	64116	MXL1F240A3	●	64124	MXL2F1224DA5	●	64138	MXL2F240A3	●	64144
MXL1F1224DA6	○	64117	MXL1F240A4	●	64125	MXL2F1224DA6	○	64139	MXL2F240A5	●	64145
MXL1F110A1	●	64118	MXL1F240A5	●	64126	MXL2F110A2	●	64140	MXL2F240A6	○	64151
MXL1F110A2	●	64119	MXL1F240A6	○	64127						

Luci fisse


Continuous light beacons

V 12÷240 (±10%)			50/60 Hz	IP 65		°C -30 +50
On			PC	autoestinguente self-extinguishing		



(13)

		V 	12 ÷ 24 ÷ 48 ÷ 110 ÷ 240				
BA 15d 5W LR BA 15d 5W		mA	430	210	100	35	22
		Cd (p)	4	3	3	2.5	2.5
BA 15d 10W LR BA 15d 10W		mA	830	420	210	90	42
		Cd (p)	6.5	4.5	4.8	3.7	3.8
OVOFMT12240DA1 		30011	OVOFMT12240DA4 		30011		
OVOFMT12240DA2 		30012	OVOFMT12240DA5 		30011		
OVOFMT12240DA3 		30013	OVOFMT12240DA6 		30011		



Kg. 0,15


Fornito senza lampada. Supplied without bulb.
Possibilità di installazione lampada a LED. LED bulb option.

OVOFMT12240DA1	●	30011	OVOFMT12240DA4	●	30014
OVOFMT12240DA2	●	30012	OVOFMT12240DA5	●	30015
OVOFMT12240DA3	●	30013	OVOFMT12240DA6	○	30016



(13)

 BA 15d 5W LR BA 15d 5W	V 	12 ÷ 24 ÷ 48 ÷ 110 ÷ 240				
	mA	430	210	100	35	22
	Cd (p)	4	3	3	2.5	2.5
BA 15d 10W LR BA 15d 10W	mA	830	420	210	90	42
	Cd (p)	6.5	4.5	4.8	3.7	3.8
OVOPG9FMT12240DA1  30031		OVOPG9FMT12240DA4  30034				
OVOPG9FMT12240DA2  30032		OVOPG9FMT12240DA5  30035				
OVOPG9FMT12240DA3  30033		OVOPG9FMT12240DA6  30036				



Kg. 0,24

Fornito senza lampada. Supplied without bulb.
Possibilità di installazione lampada a LED. LED bulb option.

OVOPG9FMT12240DA1	●	30031	OVOPG9FMT12240DA4	●	30034
OVOPG9FMT12240DA2	●	30032	OVOPG9FMT12240DA5	●	30035
OVOPG9FMT12240DA3	●	30033	OVOPG9FMT12240DA6	○	30036

Per ordinare l'opzione nera richiedere i codici. Code numbers for the black version are available on request.

Luci fisse

Continuous light beacons




(13)

V 12÷240 $\sim$ ($\pm 10\%$)	$\sim$	50/60 Hz	IP 65	$^{\circ}\text{C}$ -30 +50
On ∞		1 2 3 4 5 6	PC	autoestinguente self-extinguishing

	V $\sim$	12 ÷ 24 ÷ 48 ÷ 110 ÷ 240				
BA 15d 5W LR BA 15d 5W	mA	430	210	100	35	22
	Cd (p)	4	3	3	2.5	2.5
BA 15d 10W LR BA 15d 10W	mA	830	420	210	90	42
	Cd (p)	6.5	4.5	4.8	3.7	3.8

OVDEFMT12240DA1	●	31331	OVDEFMT12240DA4	●	31334
OVDEFMT12240DA2	●	31332	OVDEFMT12240DA5	●	31335
OVDEFMT12240DA3	●	31333	OVDEFMT12240DA6	○	31336



Kg. 0,10

Fornito senza lampada. Supplied without bulb.
Possibilità di installazione lampada a LED. LED bulb option.

Sistemi applicativi Application systems



Luci lampeggianti Flashing beacons




(13)

V 12÷48 $\sim$ -24÷240 $\sim$ ($\pm 10\%$)	$\sim$	50/60 Hz	Flash/min. 110±20	IP 65	$^{\circ}\text{C}$ -30 +50
On ∞		1 2 3 4 5 6	PC	autoestinguente self-extinguishing	

	V $\sim$	12 ÷ 24 ÷ 48	-	-		
BA 15d 5W LR BA 15d 5W	mA	430	210	100	35	22
	Cd (p)	4	3	3	2.5	2.5
BA 15d 10W LR BA 15d 10W	mA	830	420	210	90	42
	Cd (p)	6.5	4.5	4.8	3.7	3.8

OVOLMT1248D1	●	30051	OVOLMT24240A1	●	30091
OVOLMT1248D2	●	30052	OVOLMT24240A2	●	30092
OVOLMT1248D3	●	30053	OVOLMT24240A3	●	30093
OVOLMT1248D4	●	30054	OVOLMT24240A4	●	30094
OVOLMT1248D5	●	30055	OVOLMT24240A5	●	30095
OVOLMT1248D6	○	30056	OVOLMT24240A6	○	30096



Kg. 0,15

Fornito senza lampada. Supplied without bulb.
Possibilità di installazione lampada a LED. LED bulb option.

Per ordinare l'opzione nera richiedere i codici. Code numbers for the black version are available on request.